



WANJIA

Relays for advanced technology

ULTRA-MINIATURE
PC BOARD TYPE
POWER RELAY

WJ102-RELAYS



- Ultra-small type with dimensions.
- High sensitivity:200mW nominal operating power
- Sealed type available
- Low coil power consumption

SPECIFICATIONS

Contact

Item	Type	WJ102
Arrangement		1 Form C
Contact Material		Silver alloy
Contact Resistance (By voltage 6V 1A)		Max.100mOhm
Rating		
Nominal switching capacity		3A 120VAC/24VDC
Resistive load (cos φ=1)		1A 120VAC/24VDC
Inductive load (cos φ=0.75~0.8)		0.3A 120VAC 0.3A 24VDC
Max. Switching voltage		120VAC 60VDC
Max. Switching current		3A
Max. Switching power		600VA 120W
Expected life(min.ope)		
Mechanical(at 120 cpm)		1×10^7
Electrical(at 20 cpm)		1×10^5

Coil

Nominal operating power	0.2 to 0.45W
-------------------------	--------------

TYPICAL APPLICATION

- 1.Telecommunication.
- 2.Domestic appliance.

Characteristics

Item	Type	WJ102(0.36W)	WJ102(0.2W)
Operate Time		Max.8msec.	Max.10msec.
Release Time		Max.4msec.	
Operating humidity		45 to 85% RH	
Initial breakdown voltage			
Between coil & contact		500VAC (50/60Hz)for 1min.	
Between open contacts		500VAC (50/60Hz)for 1min.	
Insulation Resistance		Min.100MOhm (500 VDC)	
Ambient temperature		-30C...+60C	-30C...+75C
Temperature rise(Max.)		45deg.	25deg.
Shock	Functional	Min.10G	
Resistance	Destruction	Min.100G	
Vibration	Functional	10 to 55 Hz at double Amplitude of 1.5mm	
Resistance	Destruction	10 to 55 Hz at double Amplitude of 1.5mm	
Unit weight		Approx.3.5g	

- 3.Office machines.
- 4.Audio equipment,etc.

ORDERING INFORMATION

WJ102 - H - 1C - 12VDC

1 2 3 4

1 Part Number

2 H: High Sensitive 0.2W

3 Contact Arrangements

4 Coil Voltage